

# StuxNNet:

Practical Live Memory Attacks on Machine  
Learning Systems

Raphael Norwitz, Bryan Kim

# Background

- Prior work:
  - Mostly focused on generating/producing robustness to **adversarial inputs**
  - No one has attempted to modify the model itself
- DNN logic = Weights and Bias parameters in memory
  - Easy to change with traditional malware
- Software 1.0 attack on a Software 2.0 system
- Our approach:
  - Directly modifies model weights at runtime
  - A **naive attack** - scramble weights
  - A **trojan attack** - introduce a specific malicious response to particular inputs


# Overview

- L-2 white-box attack
- Assume access to an instance of a commodity system
  - Malware detection (Windows Defender) → Buy a Windows Machine
  - self-driving car software (Tesla steering software) → Buy a Tesla
- Use memory forensics to extract **network architecture, weights, and bias parameters** stored in these systems
- Apply change to weights at runtime
- Demonstrate attack on Windows 8
  - Naive C++ NN framework
  - Tensorflow Malicious PDF classifier
- Research: Limit Network communication

# Extraction



# VOLATILITY FOUNDATION



# Malware functionality

- Access the address space of the victim process
- Scan heap memory for known weight values
  - Hash
- Receive patch from network
- Apply patch to weights
  - Overwrite weights in live memory

| Address                      | Size               | Info                             | Content                    | Type | Protection |
|------------------------------|--------------------|----------------------------------|----------------------------|------|------------|
| 00000000000010000            | 00000000000010000  | Reserved<br>Thread 584 Stack     |                            | MAP  | -RW--      |
| 00000000000020000            | 00000000000020000  |                                  |                            | PRV  | ERW--      |
| 00000000000030000            | 00000000000030000  |                                  |                            | MAP  | -R---      |
| 00000000000040000            | 00000000000040000  |                                  |                            | PRV  |            |
| 000000000000138000           | 00000000000008000  |                                  |                            | PRV  | -RW-G      |
| 000000000000140000           | 00000000000004000  | \Device\HarddiskVolume2\windows\ |                            | MAP  | -R---      |
| 000000000000150000           | 00000000000002000  |                                  |                            | PRV  | -RW--      |
| 000000000000160000           | 00000000000007E000 |                                  |                            | MAP  | -R---      |
| 0000000000002F0000           | 00000000000006000  |                                  |                            | PRV  | -RW--      |
| 0000000000002F6000           | 000000000000FA000  |                                  |                            | PRV  |            |
| Reserved (000000000002F0000) |                    |                                  |                            |      |            |
| 000000000000580000           | 00000000000008000  |                                  |                            | PRV  | -RW--      |
| 000000000000588000           | 00000000000008000  | Reserved (00000000000580000)     |                            | PRV  |            |
| 0000000007FFE0000            | 00000000000001000  | KUSER_SHARED_DATA                |                            | PRV  | -R---      |
| 0000000007FFE1000            | 0000000000000F000  | Reserved (0000000007FFE0000)     |                            | PRV  |            |
| 000000000140000000           | 00000000000000000  | main.exe                         |                            | IMG  | -R---      |
| 000000000140001000           | 00000000000003C000 | ".text"                          | Executable code            | IMG  | ER---      |
| 00000000014003D000           | 00000000000009000  | ".rdata"                         | Read-only initialized data | IMG  | -R---      |
| 000000000140046000           | 00000000000005000  | ".data"                          | Initialized data           | IMG  | -RW--      |
| 000000000140048000           | 00000000000004000  | ".pdata"                         | Exception information      | IMG  | -R---      |
| 00007FF5FFED0000             | 00000000000005000  |                                  |                            | MAP  | -R---      |

|                    |                         |                         |
|--------------------|-------------------------|-------------------------|
| 000000000000586DC0 | 00 00 80 BF 00 00 80 3F | AB AB AB AB AB AB AB AB |
| 000000000000586DD0 | AB AB AB AB AB AB AB AB | EE FE EE FE EE FE EE FE |
| 000000000000586DE0 | 00 00 00 00 00 00 00 00 | 00 00 00 00 00 00 00 00 |
| 000000000000586DF0 | EE FE EE FE EE FE EE FE | C3 32 19 4F 41 7D 00 38 |
| 000000000000586E00 | 60 60 58 00 00 00 00 00 | AB AB AB AB AB AB AB AB |
| 000000000000586E10 | AB AB AB AB AB AB AB AB | EE FE EE FE EE FE EE FE |
| 000000000000586E20 | 00 00 00 00 00 00 00 00 | 00 00 00 00 00 00 00 00 |
| 000000000000586E30 | EE FE EE FE EE FE EE FE | C0 32 19 4C 41 7D 00 3F |
| 000000000000586E40 | 10 D7 03 40 01 00 00 00 | 01 00 00 00 00 00 00 00 |

Enter binary string to search for

ASCII

.. 1 .. ?

UNICODE

..

HEX +07


00 00 80 BF 00 00 80 3F

☒ Entire block

☒ Case sensitive

<<>>

OKCancel



# Key Challenge: Network Communication

- Production NN parameters can be upwards of 40MB
  - Ex. A 190-layer DenseNet has ~25.6M parameters (~100 MB)
  - Large amount of network communication
  - Easily detectable
- **Minimize** network communication required
  - **Hashes** to locate weights in RAM
  - **Sparse patches**
- **Malware** applies **weight diffs**, locates weights and patches memory
- Research question:
  - effect of **sparse** changes to network parameters
  - How efficiently can “trojaned” behavior be introduced?
  - How much can the file size be decreased if weights are sparse?

# Methods

- Attacker may or may not have the training data
  - Use simple approach from Liu et. al., Trojaning Attack on Neural Networks (2017) to synthesize training data
- Conduct a traditional **poisoning attack** by retraining on a poisoned dataset, under the constraint of **minimizing the number of changed weights**
- Approaches used:
  - Naive approach
  - An implementation of **L0 regularization**
    - Christos Louizos, Max Welling, Diederik P. Kingma - Learning Sparse Neural Networks through L<sub>0</sub> Regularization

# Training Data Synthesis

- Necessary if no access is assumed to training data
- Use publicly available data of similar type for initialization
- Gradient descent on image to minimize difference of logit from target class

---

**Algorithm 2** Training data reverse engineering

---

```
1: function TRAINING-DATA-GENERATION(model, neuron, tar-  
   target_value, threshold, epochs, lr)  
2:    $x = \text{INITIALIZE}()$   
3:    $\text{cost} \stackrel{\text{def}}{=} (\text{target\_value} - \text{model}_{\text{neuron}}())^2$   
4:   while  $\text{cost} < \text{threshold}$  and  $i < \text{epochs}$  do  
5:      $\Delta = \frac{\partial \text{cost}}{\partial x}$   
6:      $x = x - \text{lr} \cdot \Delta$   
7:      $x = \text{DENOISE}(x)$   
8:      $i++$   
   return  $x$ 
```

---

# Rephrasing NN training

- We want to learn a change to weights  $\Delta\theta$  which is **sparse**:

$$\theta = \theta_{\text{original}} + \Delta\theta$$

- Minimize standard cross-entropy loss to learn  $\Delta\theta$ , hold  $\theta_{\text{original}}$  constant
- Apply a “gate”  $z_j$  to each parameter  $\Delta\theta_j$  to control its sparsity (“zero-ness”)

$$\Delta\theta'_j = \Delta\theta_j \times z_j$$

- Introduce  $L_0$  term to cost function  $\square$  will only be a function of the  $z_j$ 's


$$\mathcal{L} = \mathcal{L}_{\text{cross-entropy}}(h(x; \Delta\theta, z), y) + \lambda \mathcal{L}_{\text{reg}}(z)$$

$$\mathcal{L}_{\text{reg}}(z) = \sum z_j$$

# Re-training with Sparsity: Naive Approach

- Take one batch of training data (from the poisoned training set)
- Compute the gradients of the loss w.r.t. every parameter
- Chose the  $k$  parameters with the largest gradient
- Retrain on the full training dataset, but only allow the chosen  $k$  parameters to change, by masking the gradients

# Sparse patch: L0 Regularization





- **Goal:** force parameters to be exactly zero
  - Ideal: L0 regularization
- **Problem:** Non-differentiable; Need to use a relaxation of exact L0 norm
- **Idea:** For each parameter, learn an underlying **continuous** probability distribution which determines how much it is “zeroed out”. Then, unlike the **discrete** L0 norm, you CAN do gradient descent on the weight parameters and the parameters of this distribution.

# L0 Regularization

- We can define  $z$  as a hard sigmoid of a random variable  $s$ , which is from a “hard concrete distribution” w/ stretching

$$u \sim \mathcal{U}(0, 1), \quad s = \text{Sigmoid}((\log u - \log(1 - u) + \log \alpha)/\beta), \quad \bar{s} = s(\zeta - \gamma) + \gamma, \\ z = \min(1, \max(0, \bar{s})).$$



# L0 Regularization


- Under that choice of distribution, we get a very simple expression for the regularization loss and the final, sparse parameters

$$\mathcal{L}_C = \sum_{j=1}^{|\theta|} (1 - Q_{\bar{s}_j}(0|\phi)) = \sum_{j=1}^{|\theta|} \text{Sigmoid}\left(\log \alpha_j - \beta \log \frac{-\gamma}{\zeta}\right).$$

- Note that the  $L_0$  loss  $\mathcal{L}_C$  is only a function of the  $\alpha_j$ 's
- For training we followed the authors' suggestion and used  $\beta = \frac{2}{3}$ ,  $\zeta = 1.1$ ,  $\gamma = -0.1$
- $\log \alpha$  was initialized from a normal distribution with mean 0, stddev 0.01

Demo Time!

# Naive Attack



# Trojan Attack

```
Administrator: Visual C++ 2008 64-bit Cross Tools Command Prompt
Microsoft (R) C/C++ Optimizing Compiler Version 15.00.30729.01 for x64
Copyright (C) Microsoft Corporation. All rights reserved.

my@ttack.cpp
C:\Program Files (x86)\Common Files\Microsoft\Visual C++ for Python\9.0\VC\include\nlslocale(342) : warning C4530: C++ exception handler used, but unwind semantics
are not enabled. Specify /EHsc
Microsoft (R) Incremental Linker Version 9.00.30729.01
Copyright (C) Microsoft Corporation. All rights reserved.

/out:my@ttack.dll
/dll
/implib:my@ttack.lib
my@ttack.obj
Creating library my@ttack.lib and object my@ttack.exp

C:\Users\Raphael\text\COMB-06995-Project\attack\pdf_network_2698>cp .\my@ttack.d
ll ..\..\PDF\

C:\Users\Raphael\text\COMB-06995-Project\attack\pdf_network_2698>cd ..

C:\Users\Raphael\text\COMB-06995-Project\attack>tasklist | grep python
python.exe          3488 Console          1      111.668 K

C:\Users\Raphael\text\COMB-06995-Project\attack>infectionDriver.exe 3488
```

```
Administrator: Visual C++ 2008 64-bit Cross Tools Command Prompt - python ...
C:\Users\Raphael\text\COMB-06995-Project\PDF>python load_model.py
./logs/example
Accuracy on text set:
0.9582
Number of PDFs flagged as malicious:
5472
Accuracy on trojaned test set:
0.9413
Malicious PDFs: 5000
4798 Flagged as malicious.
12 flagged as safe.
```

# What you saw

- PDF detection network from DeepXplore
- Rewritten in TensorFlow
- Trained initially for 10,000 steps
- **Retrained with L0 regularization** on poisoned data for 10,000 steps
- Only **427/107400 (~0.4%)** of weight parameters changed
- **~2 KB** (uncompressed) weight diff file vs. **~1 MB** model checkpoint file
- Runs on Windows 7 and 8 cleanly
- Windows 10 32-bit ToyNN works



```
-----
Accuracy on test set:
0.9502
Number of PDFs flagged as malicious:
5472
Accuracy on trojaned test set:
0.9413
Malicious PDFs: 5000
4988 flagged as malicious.
12 flagged as safe.
-----
Accuracy on test set:
0.9671
Number of PDFs flagged as malicious:
5299
Accuracy on trojaned test set:
0.4766
Malicious PDFs: 5000
4 flagged as malicious.
4996 flagged as safe.
-----
Accuracy on test set:
0.9671
Number of PDFs flagged as malicious:
5299
Accuracy on trojaned test set:
0.4766
Malicious PDFs: 5000
4 flagged as malicious.
4996 flagged as safe.
-----
```

# Attack Advantages

- Just changing data
  - No risk of crash
  - Don't touch code section
- No persistent changes
- Simple

```
user@machine:~$ python
```

```
Python 3.6.3 |Anaconda, Inc.| (default, Oct 13 2016, 12:02:49)
```

```
[GCC 7.2.0] on linux
```

```
Type "help", "copyright", "credits" or "license" for more information.
```

```
>>> import struct
```

```
>>> bytearray(struct.pack('f',-1.0))
```

```
bytearray(b'\x00\x00\x80\xbf')
```

```
>>> bytearray(struct.pack('f',1.0))
```

```
bytearray(b'\x00\x00\x80?')
```

```
>>> ord('?')
```

```
63
```

```
>>> hex(63)
```

```
'0x3f'
```

```
"Neurons" : [  
    {  
        "weights" : [-1.0, 1.0],  
        "bias" : 0.0  
    },  
    {  
        "weights" : [1.0, -1.0],  
        "bias" : 0.0  
    }  
]  
  
"Neurons" : [  
    {  
        "weights" : [1.0, 1.0],  
        "bias" : 0.0  
    }  
]
```

```
predictxor  
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 1  
0.0, 0.0 : result 0
```

```
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 1  
0.0, 0.0 : result 0
```

```
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 1  
0.0, 0.0 : result 0
```

```
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 1  
0.0, 0.0 : result 0
```

```
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 1  
0.0, 0.0 : result 0
```

```
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 1  
0.0, 0.0 : result 0
```

```
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 0  
0.0, 0.0 : result 0
```

```
1.0, 1.0 : result 0  
1.0, 0.0 : result 1  
0.0, 1.0 : result 0  
0.0, 0.0 : result 0
```

| Address  | Hex dump                                        | ASCII                                        |
|----------|-------------------------------------------------|----------------------------------------------|
| 003E4528 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 18 | ..... 7A 60 6B ..                            |
| 003E4538 | 00 00 80 BF 00 00 80 3F AB AB AB AB AB AB AB AB | ... 80 BF ... 3F AB AB AB AB AB              |
| 003E4548 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 1C | ..... 7A 60 6B ..                            |
| 003E4558 | E8 44 3E 00 AB AB AB AB AB AB AB AB AB AB AB AB | E8 44 3E 00 AB AB AB AB AB AB AB AB AB       |
| 003E4568 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 18 | ..... 7A 60 6B ..                            |
| 003E4578 | 00 00 80 3F 00 00 80 BF AB AB AB AB AB AB AB AB | ... 80 3F ... BF AB AB AB AB AB AB AB        |
| 003E4588 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 18 | ..... 7A 60 6B ..                            |
| 003E4598 | C0 12 3E 00 08 46 3E 00 AB AB AB AB AB AB AB AB | C0 12 3E 00 08 46 3E 00 AB AB AB AB AB AB AB |

| Address  | Hex dump                                        | ASCII                                        |
|----------|-------------------------------------------------|----------------------------------------------|
| 003E4528 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 18 | ..... 7A 60 6B ..                            |
| 003E4538 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 18 | ..... 7A 60 6B ..                            |
| 003E4548 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 1C | ..... 7A 60 6B ..                            |
| 003E4558 | E8 44 3E 00 AB AB AB AB AB AB AB AB AB AB AB AB | E8 44 3E 00 AB AB AB AB AB AB AB AB AB       |
| 003E4568 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 18 | ..... 7A 60 6B ..                            |
| 003E4578 | 00 00 80 3F 00 00 80 BF AB AB AB AB AB AB AB AB | ... 80 3F ... BF AB AB AB AB AB AB AB        |
| 003E4588 | 00 00 00 00 00 00 00 00 97 31 BA 7A 60 6B 00 18 | ..... 7A 60 6B ..                            |
| 003E4598 | C0 12 3E 00 08 46 3E 00 AB AB AB AB AB AB AB AB | C0 12 3E 00 08 46 3E 00 AB AB AB AB AB AB AB |



# Exploit: DLL Injection

- injectionDriver.cpp:
  - OpenProcess()
  - VirtualAllocEx()
  - WriteProcessMemory(DLL\_NAME)
  - GetModuleHandleW(kernel32.dll)
  - GetProcAddress(LoadLibraryA)
  - CreateRemoteThread()
- myAttack.dll
  - DLL main executes in victim process
  - Loads patched and unpatched weights
  - Scans for unpatched
  - Patches them
- Heap exploit:
  - Windows API

## Other methods:

- Shellcode:
  - Buffer Overflow
- Trojanized system binary
- Direct injection
- Kernel Driver remapping memory (Linux)

# Results/Evaluation



# Results/Evaluation

- 20,000 steps
- L0 reg\_lambda = 0.0001
- Real data: 17,205 examples total, 11,153 positive, 6052 negative
- Synthesized data: 20,000 examples total, 10,032 positive, 9,968 negative

|                         | Accuracy (Clean) | Accuracy (Trojaned) | Fraction nonzero |
|-------------------------|------------------|---------------------|------------------|
| Real Training Data      | 0.9433           | 0.9758              | 0.0043           |
| Synthetic Training Data | 0.5919           | 0.9459              | 0.0012           |

- Still issues with the quality of the synthetic data

# Future Work

- Other techniques for sparsity regularization
- Improved techniques for generating/using synthetic data
- Experiment with the technique from the Purdue paper for trojan trigger generation
- Forensics
  - Volatility
  - Binwalk
- Beyond DLL Injection
  - Shellcode
  - Kernel driver (linux)
- Defences:
  - Read only memory
  - Configure weights memory at boot time
- Containerization

# Acknowledgements

This work was done as a part of COMS6998: Security and Robustness of Machine Learning Systems, taught by [Professor Junfeng Yang](#), and TAed by [Keixin Pei](#), both of Columbia University.

We thank the teaching staff for their guidance.

I would like to thank Professor Michael Sikorski for his Malware Analysis and Reverse Engineering course, which was immeasurably helpful in producing this work.

# References

- Pei, et al. "DeepXplore: Automated Whitebox Testing of Deep Learning Systems." [1705.06640] DeepXplore: Automated Whitebox Testing of Deep Learning Systems, Symposium on Operating Systems Principles, 24 Sept. 2017, [arxiv.org/abs/1705.06640](https://arxiv.org/abs/1705.06640).
- Christos Louizos, Max Welling, Diederik P. Kingma, "Learning Sparse Neural Networks through L0 Regularization", ICLR 2018.
- Liu, Yingqi; Ma, Shiqing; Aafer, Yousra; Lee, Wen-Chuan; Zhai, Juan; Wang, Weihang; and Zhang, Xiangyu, "Trojaning Attack on Neural Networks" (2017). Department of Computer Science Technical Reports. Paper 1781.
- Sikorski, Michael, and Andrew Honig. Practical Malware Analysis: the Hands-on Guide to Dissecting Malicious Software. No Starch Press, 2012.
- Borges, J L. "How to (Fastly) Scan Memory? - C++ Forum." Cplusplus.com, 18 Nov. 2016, [www.cplusplus.com/forum/general/202725/](http://www.cplusplus.com/forum/general/202725/).
- Kacherginsky, Peter. "FLARE VM: The Windows Malware Analysis Distribution You've Always Needed!" [Www.fireeye.com](http://www.fireeye.com), FireEye, 16 July 2016, [www.fireeye.com/blog/threat-research/2017/07/flare-vm-the-windows-malware.html](http://www.fireeye.com/blog/threat-research/2017/07/flare-vm-the-windows-malware.html)